

INSTALLATION INSTRUCTIONS

Always follow appropriate safety precautions when servicing sewer manholes. This includes personnel protection, traffic, and ventilation. Sewer gases are dangerous and contain hazardous, poisonous, flammable and explosive gases. Only experienced trained workers following OSHA's safety requirements should work around sewer manholes.

Never leave a manhole uncovered and unsupervised. Place barrier cones at service area.

1. Remove manhole cover.
2. Clean frame under cover.
3. Measure and double check frame size and type before insert is installed.
4. Test funnel fit by placing lightly on frame. If not sitting flat inspect for any obstructions or irregularities. A sponge gasket or silicone may be used to help create a tight seal. If it sits perfectly flat then leave in place.
5. Drop housing into funnel and check to insure a tight fit.

Contact Inventive Resources, Inc. at 209-545-1663 to order replacement cartridges.

- To maintain optimum performance, suggested filter replacement time is every 12 months or sooner if odor is present, as spent media can coagulate and plug the filtration unit, causing a reduction in air flow.
- The life of the odor absorbing cartridge at each manhole varies depending on the sewer system activity, sewer gas concentration and ambient conditions.
- When multiple MOE units are used at one site it is suggested that spare cartridges be available for problem areas.

SERVICING INSTRUCTIONS

1. Remove manhole cover.
2. Remove MOE cartridge from housing.
3. Wash out housing and funnel if necessary.
4. Place new cartridge in housing and replace manhole cover.

Install Date: _____ Address: _____

Installed By: _____

Facility: _____ Contact# _____

Inventive Resources, Inc.
5038 Salida Blvd / PO Box 1316
Salida, CA 95368
Phone 209.545.1663
Email: info@iriproducts.com

